

DATA SHEET

Powered Tug - M6.5 Tow Motor



ZALLYS M6.5

Standard features include: 24V 100Ah traction batteries, 4.5km/h speed, 6000kg capacity, 7500kg* capacity, 935mm wheelbase, 730mm frame height, 1200mm machine length, 450mm machine width, 250mm wheel base, 1000mm frame height, 1500mm machine weight, 1500W electric motor, 2 traction batteries.

Optional features include: 24V 150Ah traction batteries, 5.5km/h speed, 8000kg capacity, 10000kg* capacity, 1100mm wheelbase, 850mm frame height, 1500mm machine length, 500mm machine width, 300mm wheel base, 1200mm frame height, 1800mm machine weight, 2000W electric motor, 3 traction batteries.

Additional features include: 24V 200Ah traction batteries, 6.5km/h speed, 10000kg capacity, 12000kg* capacity, 1300mm wheelbase, 1000mm frame height, 1800mm machine length, 600mm machine width, 400mm wheel base, 1500mm frame height, 2200mm machine weight, 2500W electric motor, 4 traction batteries.

Other features include: 24V 250Ah traction batteries, 7.5km/h speed, 12000kg capacity, 15000kg* capacity, 1500mm wheelbase, 1200mm frame height, 2200mm machine length, 700mm machine width, 500mm wheel base, 1800mm frame height, 2600mm machine weight, 3000W electric motor, 5 traction batteries.

Additional features include: 24V 300Ah traction batteries, 8.5km/h speed, 15000kg capacity, 18000kg* capacity, 1800mm wheelbase, 1500mm frame height, 2800mm machine length, 800mm machine width, 600mm wheel base, 2100mm frame height, 3000mm machine weight, 3500W electric motor, 6 traction batteries.

Machine length:	1500mm
Machine width:	450mm
Wheel base:	250mm
Frame height:	1000mm
Machine weight:	1500kg
Electric motor:	1500W
2 traction batteries:	24V 100Ah



M6.5 is a standard model.